

	T008	T010	T031	T041	T170	T172	T170/T172 ISC
Application Area / Temperature Range							
Operating Room			X	X	X	X	
Refrigeration Room (0 °C to +8 °C)	X						X
Freezer Room (0 °C to -28 °C)		X					X
Special Solutions (PU160 down to -80 °C)		X					
Dimensions [mm]							
Max. Width (Clearance)	1500*	1500*	1500*	1500*	1300	1300	1300
Max. Height (Clearance)	3500**	3500**	3500**	3500**	2800	2800	2800
Min. Width (Clearance)	500	500	500	600	600	600	600
Min. Height (Clearance)	420	420	420	420	1750	1750	1750
Door Leaf Thickness	85	120/160	65	85	62	62	80
Fire Resistance / Fire Rating			T30	T90	T30	T90	T30/T90
Double Leaf Variant	T018	T012	T032	T042	T171	T173	
Materials							
Stainless Steel (V2A 1.4301, V4A 1.4404)	V2A (1.4301), V4A (1.4404), brushed, streaked, matt, linen finish				V2A (1.4301) K240, brushed, streaked (door leaf)		
Galvanized Steel (Coated)	RAL9002, RAL9005, RAL9010, RAL7016, RAL7035				RAL9007, RAL9010, RAL7016		
Other RAL Colors on request	X						
Frame							

Installation in Brickwork	Block Frame, Flat Frame, Surrounding Frame, Corner Frame				Block Frame, Surrounding Frame		
Installation in Panel (Sandwich Panels)	Foamed Stock (500), Clamp Frame				Block Frame		
Threshold	Optional available						
Hinges	Standard DIN Hinge / Rising Hinge						
Handle Types							
Press Lever	X	X	X	X			
Oskar Magnet Lock	X	X	X	X			
Handle Bar	X	X	X	X			
Hardware Set	X		X	X	X	X	X
Various Other Designs							
Special Equipment							
Pipe Passage	X		X	X			

)